

CSM-430D-06

Rubber Band Splicing Machine

拼橡筋机



作为电子套结机它不仅实现了 **3200rpm** 的 **业内最高缝制速度**，还能快速启动或停止。

通过提高切线速度以及抬压脚操作大幅度缩短了机器的操作循环时间。

As an electronic bar tacking machine, it does not only realize the maximum sewing speed of 3200rpm in the industry, but can has quick start or stop. Through improving the thread cutting speed and presser foot operation, it shortens the operation cycle time of the machine in large scale.

在纵向**40mm**的缝制范围内，可以应对多种套结形状。缝制花样可根据工艺要求自由设定。

In the vertical sewing range of 40mm, it can respond to various bar tacking shapes.

采用了**灵活的张力**，通过操作控制盘可以设定面线的张力以对应各种缝制条件，数据可以储存以及再使用。

Applying flexible tensile force, it can set the tensile force of the top stitch through operating the control panel, so as to conform to each sewing condition. The data can be stored and reused.

先进的干式机头化技术，在面部(针杆部、挑线杆部)实现了无油化。彻底消除了缝制品被机油所污染。

Through advanced dry machine head technology, it can realize oil-free on the surface (needle bar, take-up lever).

Thoroughly remove the pollution of engine oil to the sewing products.

CSM-438D

Direct Drive Lockstitch Electronic Button Attaching Machine

直接驱动式平缝电脑钉扣机



高速缝纫且线迹美观，实现了 **业内最快** 的 **循环时间**。

With high-speed sewing and beautiful stitch, it realize the fastest cycle time in the industry.

实现了 **优良的缝纫品质和高生产效率**。

It realizes excellent sewing quality and high production efficiency.

转速为2,700rpm / The rotation speed is 2,700rpm

最大6.4~6.4 mm / Maximum 6.4~6.4 mm

最大13mm / Maximum 13mm

半回转标准旋梭 / Semi-rotary standard rotating shuttle

已输入49种缝纫图案 / It has input 49 kinds of sewing pattern

外径8-30mm / External diameter 8-30mm

可用于缝制的纽扣尺寸 / (20mm以上的用选购纽扣夹组件B)

Size Of Button That Can Be Sewed /

(for that above 20mm, use optional button grip component B)

